

P/N MS24693-272B

Description

length: 1/2", thread: 10-32, countersunk, flat head, corrosion resistant steel, black oxide coated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS24693272B

Minimum Qty (MOQ): 100

NSN: 5305-01-070-2951


EAR99 ECCN:

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24693-272B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.417 Inches Nominal
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66,300 Series Fed Std Single Material Response
Screw Surface Treatment:	Passivate And Oxide
Screw Surface Treatment Document And Classification:	66,300 Series Fed Std Single Treatment Response And Mil-c-13924 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693-272B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS24693-272B and selecting the quantity you