

P/N MS24693-274B

Description

length: 3/4, thread: 10-32, corrosion resistant steel, black oxide coated, countersunk, flat head, machine screw, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS24693274B

Minimum Qty (MOQ): 100

NSN: 5305-00-063-3507

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS24693-274B Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.688 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.333 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 1010 Or Steel |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec 1st Material Response Or Qq-s-631 Fed Spec 1st Material Response Or Qq-s-634 Fed Spec 1st Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693-274B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.