

Description

MS24693-294B Machine Screw, black

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS24693294B
Minimum Qty (MOQ):	50
NSN:	5305-01-265-4901
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N MS24693-294B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.226 Inches Minimum And 0.328 Inches Maximum
Fastener Length:	0.468 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Oxide
Screw Surface Treatment Document And Classification:	Mil-c-13924 Mil Spec Single Treatment Response
Color:	Black
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-294B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.