



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N MS24693-2B**

## Description

length: 1/4in., thread: 4-40, countersunk flat head, black oxide, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS246932B
Minimum Qty (MOQ):	100
NSN:	5305-00-031-1042
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS24693-2B Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.120 Inches Minimum And 0.201 Inches Maximum
<b>Fastener Length:</b>	0.219 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.191 Inches Minimum And 0.225 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	Qq-s-763 Fed Spec All Material Responses Or 66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Oxide
<b>Screw Surface Treatment Document And Classification:</b>	Mil-c-13924,cl 4 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 3c Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-2B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.