

Description

Fastener Length: 1-3/4", Thread: 6-32, Thread Length: 1-11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2469338B |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-067-3376 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS24693-38B Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.566 Inches Minimum And 1.690 Inches Maximum |
| Fastener Length: | 1.688 Inches Minimum And 1.750 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.238 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Oxide |
| Screw Surface Treatment Document And Classification: | Mil-c-13924 Cl 4 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-38B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.