

**Description**

Fastener Length: 3/8", Thread: 4-40, Thread Length: 5/16", MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS246934B                                 |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-094-3430                          |
| Schedule B:             | 7318.15.9000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS24693-4B Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.245 Inches Minimum And 0.326 Inches Maximum   |
| <b>Fastener Length:</b>                                     | 0.344 Inches Minimum And 0.375 Inches Maximum   |
| <b>Head Style:</b>  | Flat Countersunk  |
| <b>Head Diameter:</b>                                       | 0.191 Inches Minimum And 0.225 Inches Maximum   |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                             | 0.112 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 40  |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| <b>Screw Material:</b>                                      | Steel Corrosion Resisting   |
| <b>Screw Material Document And Classification:</b>          | Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8 Assn Std Single Material Response |
| <b>Screw Surface Treatment:</b>                             | Oxide   |
| <b>Screw Surface Treatment Document And Classification:</b> | Mil-c-13924,cI 4 Mil Spec Single Treatment Response   |
| <b>Thread Series Designator:</b>                            | Unc   |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 3c Style   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-4B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.