

**Description**

length: 7/16in., thread: 4-40, black oxide, corrosion resistant, countersunk flat head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS246935B
Minimum Qty (MOQ):	100
NSN:	5305-00-451-8590
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS24693-5B Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.308 Inches Minimum And 0.389 Inches Maximum
<b>Fastener Length:</b>	0.407 Inches Minimum And 0.438 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.191 Inches Minimum And 0.225 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8 Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-ms24693-5b National Std/spec
<b>Nondefinitive Spec/std Data:</b>	3 Type And 3c Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-5B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.