

Description

Fastener Length: 1-63/64", Thread: 8-32, Thread Length: 1-59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2469362B
Minimum Qty (MOQ):	60 EA
NSN:	5305-01-096-7340
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24693-62B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.804 Inches Minimum And 1.928 Inches Maximum
Fastener Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Oxide
Screw Surface Treatment Document And Classification:	Mil-c-13924,cl 4 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-62B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.