

Description

Fastener Length: 5/8", Thread: 4-40, Thread Length: 9/16", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS246937B
Minimum Qty (MOQ):	100
NSN:	5305-00-340-4749
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS24693-7B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.495 Inches Minimum And 0.576 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	Fed-std66 Fed Std All Material Responses
Screw Surface Treatment:	Oxide
Screw Surface Treatment Document And Classification:	Mil-c-13924,cl 4 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-7B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.