

**Description**

Fastener Length: 3/8", Thread: 6-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693A26](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS24693A26          |
| Minimum Qty (MOQ):      | 25                  |
| NSN:                    | 5305-00-051-6882    |
| Schedule B:             | 7616.10.9090        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE  
AVAILABLE

## P/N MS24693-A26 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.253 Inches Minimum  |
| <b>Fastener Length:</b>                                     | 0.375 Inches Nominal  |
| <b>Head Style:</b>  | Flat Countersunk  |
| <b>Head Diameter:</b>                                       | 0.238 Inches Minimum And 0.279 Inches Maximum   |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 62000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| <b>Screw Material:</b>                                      | Aluminum Alloy 2024 Or Aluminum Alloy 2017  |
| <b>Screw Material Document And Classification:</b>          | Qq-a-200 Fed Spec 1st Material Response Or Qq-a-225 Fed Spec 1st Material Response Or Qq-a-225 Fed Spec 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Anodize   |
| <b>Screw Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response   |
| <b>Thread Series Designator:</b>                            | Unc   |
| <b>Nondefinitive Spec/std Data:</b>                         | 2 Type And 3c Style   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-A26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.