

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693A26](#)

SKU / Model:	MS24693A26
Minimum Qty (MOQ):	25
NSN:	5305-00-051-6882
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws

NO IMAGE
AVAILABLE

P/N MS24693-A26 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.253 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Aluminum Alloy 2024 Or Aluminum Alloy 2017
Screw Material Document And Classification:	Qq-a-200 Fed Spec 1st Material Response Or Qq-a-225 Fed Spec 1st Material Response Or Qq-a-225 Fed Spec 2nd Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-A26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.