

**Description**

Fastener Length: 3/8", Thread: 4-40, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS24693A4
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-078-3699
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N MS24693-A4 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.264 Inches Minimum
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.191 Inches Minimum And 0.225 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Aluminum Alloy 2024 Or Aluminum Alloy 2017
<b>Screw Material Document And Classification:</b>	Qq-a-200/3 Fed Spec 1st Material Response Or Qq-a-225/6 Fed Spec 1st Material Response Or Qq-a-225/5 Fed Spec 2nd Material Response
<b>Screw Surface Treatment:</b>	Anodize
<b>Screw Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 3c Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.