

Description

Fastener Length: 7/16", Thread: 4-40, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693A5](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | MS24693A5 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-838-5053 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 013680, Alum Screws |

NO IMAGE
AVAILABLE

P/N MS24693-A5 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.388 Inches Minimum And 0.438 Inches Maximum |
| Fastener Length: | 0.406 Inches Minimum And 0.438 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.191 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-225/6 Fed Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-A5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.