

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS24693B26 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5305-01-094-0329 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS24693-B26 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.222 Inches Minimum And 0.315 Inches Maximum |
| Fastener Length: | 0.344 Inches Minimum And 0.375 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.238 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-B26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.