

Description

Fastener Length: 7/16", Thread: 6-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693B27
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-332-8611
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS24693-B27 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.284 Inches Minimum And 0.437 Inches Maximum
Fastener Length:	0.406 Inches Minimum And 0.437 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy 268 Or Copper Alloy 260 Or Copper Alloy 230 Or Copper Alloy 377 Or Copper Alloy 360 Or Copper Alloy 353 Or Copper Alloy 270 Or Copper Alloy 274 Or Copper Alloy 462 Or Copper Alloy 464 Or Copper Alloy 482 Or Copper Alloy 485 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 757 Or Copper Alloy 764 Or Copper Alloy 770 Or Copper Alloy 240 Or Copper Alloy 342
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3 Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-B27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.