



★ FASTENERS

Military-Fasteners.com

P/N MS24693-B29

Description

Fastener Length: 21/32", Thread: 6-32, Thread Length: 17/32", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24693B29
Minimum Qty (MOQ):	100
NSN:	5305-00-329-8848
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS24693-B29 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.472 Inches Minimum And 0.534 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.656 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-w-321 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Schedule

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-B29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.