

Description

Fastener Length: 1-", Thread: 6-32, Thread Length: 1-"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS24693B32 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-103-1155 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N MS24693-B32 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Nominal |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.257 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 500 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-w-321 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-B32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.