

Description

Thread: 4-40, Thread Length: 11-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693B6](#)

SKU / Model:	MS24693B6
Minimum Qty (MOQ):	25
NSN:	5305-01-375-6210
Schedule B:	7415.39.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS24693-B6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	11.913 Millimeters Minimum And 12.700 Millimeters Maximum
Fastener Length:	11.913 Millimeters Minimum And 12.700 Millimeters Maximum
Head Style:	Flat Countersunk
Head Diameter:	5.258 Millimeters Minimum And 5.715 Millimeters Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-B6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.