

Description

Screw part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693BB2](#)

SKU / Model:	MS24693BB2
Minimum Qty (MOQ):	100
NSN:	5305-00-842-5198
Schedule B:	7415.39.0000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N MS24693-BB2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.169 Inches Minimum And 0.219 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 270 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 764 Or Copper Alloy 770
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-BB2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.