



Military-Fasteners.com

P/N MS24693-BB26

## Description

length: 3/8", thread: 6-32, countersunk, flat head, black brass

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                                            |
|-------------------------|--------------------------------------------|
| SKU / Model:            | MS24693BB26                                |
| Minimum Qty (MOQ):      | 100                                        |
| NSN:                    | 5305-00-958-9546                           |
| Schedule B:             | 7415.33.8050                               |
| ECCN:                   | EAR99                                      |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |



\* See page 2 for technical characteristics

# P/N MS24693-BB26 Specifications

|                           |                                                                                                                                                                                                                                                                                      |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Thread Class:             | 2a                                                                                                                                                                                                                                                                                   |
| Thread Direction:         | Right-hand                                                                                                                                                                                                                                                                           |
| Thread Length:            | 0.222 Inches Minimum And 0.284 Inches Maximum                                                                                                                                                                                                                                        |
| Fastener Length:          | 0.344 Inches Minimum And 0.375 Inches Maximum                                                                                                                                                                                                                                        |
| Head Style:               | Flat Countersunk                                                                                                                                                                                                                                                                     |
| Head Diameter:            | 0.238 Inches Minimum And 0.279 Inches Maximum                                                                                                                                                                                                                                        |
| Internal Drive Style:     | Cross Recess Type 1                                                                                                                                                                                                                                                                  |
| Nominal Thread Diameter:  | 0.138 Inches                                                                                                                                                                                                                                                                         |
| Thread Quantity Per Inch: | 32                                                                                                                                                                                                                                                                                   |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch                                                                                                                                                                                                                                                         |
| Countersink Angle:        | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                                                                                                                                                                                                                       |
| Screw Material:           | Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 270 Or Copper Alloy 274 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 770 |
| Thread Series Designator: | Unc                                                                                                                                                                                                                                                                                  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-BB26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.