

# P/N MS24693-BB28

## **Description**

Machine Screw part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

## MS24693BB28

SKU / Model: MS24693BB28

Minimum Qty (MOQ): 100

NSN: 5305-00-958-9549

Schedule B: 7415.33.8050

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24693-BB28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.347 Inches Minimum And 0.409 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 270 Or Copper Alloy 274 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 770
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693-BB28">https://military-fasteners.com/screws/machine+screws/MS24693-BB28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.