

Description

Fastener Length: 1-3/4", Thread: 1/4-20, Thread Length: 1-5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693C104](#)

SKU / Model:	MS24693C104
Minimum Qty (MOQ):	50
NSN:	5305-00-152-5653
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-C104 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.478 Inches Minimum And 1.640 Inches Maximum
Fastener Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Avenger Class Mcm; Helicopter, Advance Attack, Ah-1w; Osprey Class Mhc; Helicopter, Carrier Based Asw, Sh-60f; Missile, Air-to-air, Sparrow (aim-7); Support Equipment, B-52 Aircraft; Helicopter, Search And Rescue, Hh-60h; Helicopter, Mh-53e; Helicopter, Uscg Search And Rescue, Hh-60j; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130)
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C104> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.