

P/N MS24693-C110

Military-Fasteners.com

### Description

MS24693-C110 Machine Screw

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### MS24693C110

SKU / Model:	MS24693C110
Minimum Qty (MOQ):	10
NSN:	5305-01-048-1120
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS24693-C110 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	2.696 Inches Minimum And 2.890 Inches Maximum
Fastener Length:	2.906 Inches Minimum And 3.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

## How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS24693-C110</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.