

## Description

Fastener Length: 0-63/64", Thread: 1/4-18, Thread Length: 55/64", flat countersunk head, coarse thread, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[MS24693C120](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS24693C120                               |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-00-455-9960                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS24693-C120 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 2a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.720 Inches Minimum And 0.862 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.969 Inches Minimum And 1.000 Inches Maximum  |
| <b>Head Style:</b>  | Flat Countersunk   |
| <b>Head Diameter:</b>                                       | 0.556 Inches Minimum And 0.635 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.312 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 18   |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch   |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Screw Material:</b>                                      | Steel Corrosion Resisting Or Steel   |
| <b>Screw Material Document And Classification:</b>          | Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Passivate  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response   |
| <b>Thread Series Designator:</b>                            | Unc  |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 3c Style  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.