



★ FASTENERS

Military-Fasteners.com

P/N MS24693-C16

Description

Length: 1/8in., Thread: 2-56, Thread Length: 1/8in., 80,000 psi tensile strength, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693C16](#)

SKU / Model:	MS24693C16
Minimum Qty (MOQ):	100
NSN:	5305-01-205-3410
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-C16 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.037 Inches Minimum And 0.088 Inches Maximum
Fastener Length:	0.110 Inches Minimum And 0.125 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.143 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.