

Description

MS24693-C17 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693C17](#)

SKU / Model:	MS24693C17
Minimum Qty (MOQ):	100
NSN:	5305-01-197-4642
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-C17 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.067 Inches Minimum And 0.119 Inches Maximum
Fastener Length:	0.140 Inches Minimum And 0.156 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.143 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Assn Std All Material Responses
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.