

**Description**

Fastener Length: 3/8", Thread: 4-48, Thread Length: 7/32", MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24693C2-04](#) [MS24693C204](#)

SKU / Model:	MS24693C204
Minimum Qty (MOQ):	100
NSN:	5305-01-174-5379
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS24693-C204 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.226 Inches Nominal
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.191 Inches Minimum And 0.225 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	48
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 100.0 Degrees Maximum
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	96906-ms24693c204 Government Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C204> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.