

Description

Fastener Length: 3/8", Thread: 4-48, Thread Length: 7/32", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693C2-04](#) [MS24693C204](#)

| | |
|-------------------------|---|
| SKU / Model: | MS24693C204 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-01-174-5379 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693-C204 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.226 Inches Nominal |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.191 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 48 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 100.0 Degrees Maximum |
| Screw Material: | Steel Corrosion Resisting |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 96906-ms24693c204 Government Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C204> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.