

Description

Fastener Length: 9/64", Thread: 0-80, Thread Length: 3/32", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

MS24693C219

SKU / Model:	MS24693C219
Minimum Qty (MOQ):	100
NSN:	5305-01-211-0660
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-C219 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.089 Inches Minimum And 0.130 Inches Maximum
Fastener Length:	0.140 Inches Minimum And 0.156 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.096 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 302b Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 384 Or Steel Comp 385 Or Steel Comp 303 Plus X Or Steel Comp 303cu Or Steel Comp 303ma
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C219> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.