

P/N MS24693-C249

Description

Machine Screw part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693C249

SKU / Model: MS24693C249

Minimum Qty (MOQ): 25

NSN: 5305-00-107-2003

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS24693-C249 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.279 Inches Minimum And 0.366 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 3c Style
Departure From Cited Designator:	As Modified By Material

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693-C249 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.