

Description

Fastener Length: 3/4", Thread: 8-36, Thread Length: 3/4", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693C252](#)

SKU / Model:	MS24693C252
Minimum Qty (MOQ):	25
NSN:	5305-01-586-9120
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24693-C252 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Nominal
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.308 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type II
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw Machine Flat Countersunk Head 100 Degrees Cross Recessed Unc-2a And Unf-2a
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C252> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.