

**Description**

length: 1/4", thread: 10-32, countersunk, flat head, corrosion resistant steel, MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24693C268](#)

SKU / Model:	MS24693C268
Minimum Qty (MOQ):	100
NSN:	5305-00-900-0593
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS24693-C268 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Fastener Length:</b>	0.219 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.333 Inches Minimum And 0.385 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C268> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.