

Description

length: 5-16, thread: 10-32, countersunk, flat head, corrosion resistant steel, MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693C269](#)

SKU / Model:	MS24693C269
Minimum Qty (MOQ):	100
NSN:	5305-00-781-5662
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-C269 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 304
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C269> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.