

P/N MS24693-C276

Military-Fasteners.com

### Description

length 1", thread 10-32, flat head, corrosion resistant, MS24693 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS24693C276	
SKU / Model:	MS24693C276
Minimum Qty (MOQ):	100
NSN:	5305-00-781-5663
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS24693-C276 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

# **How to Order**

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS24693-C276</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.