

**Description**

MS24693-C277 Machine Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693C277](#)

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS24693C277                               |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-781-5665                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS24693-C277 Specifications

|                                                    |                                                    |
|----------------------------------------------------|----------------------------------------------------|
| <b>Thread Class:</b>                               | 2a                                                 |
| <b>Thread Direction:</b>                           | Right-hand                                         |
| <b>Thread Length:</b>                              | 1.063 Inches Minimum And 1.125 Inches Maximum      |
| <b>Fastener Length:</b>                            | 1.125 Inches Nominal                               |
| <b>Head Style:</b>                                 | Flat Countersunk                                   |
| <b>Head Diameter:</b>                              | 0.333 Inches Minimum And 0.385 Inches Maximum      |
| <b>Internal Drive Style:</b>                       | Cross Recess Type 1                                |
| <b>Nominal Thread Diameter:</b>                    | 0.190 Inches                                       |
| <b>Thread Quantity Per Inch:</b>                   | 32                                                 |
| <b>Minimum Tensile Strength:</b>                   | 80000 Pounds Per Square Inch                       |
| <b>Countersink Angle:</b>                          | 99.0 Degrees Minimum And 101.0 Degrees Maximum     |
| <b>Screw Material:</b>                             | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 |
| <b>Screw Material Document And Classification:</b> | 66 Fed Std All Material Responses                  |
| <b>Screw Surface Treatment:</b>                    | Passivate                                          |
| <b>Thread Series Designator:</b>                   | Unf                                                |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C277> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.