



Military-Fasteners.com

P/N MS24693-C28

## Description

Machine Screw 5305-00-066-7327, MS24693-C28 Corrosion resistant steel length: 1/2in. thread: 6-32 countersunk flat head screw, 5305-00-066-7327

\* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

## Additional Information

### Alternate Part Numbers

[MS24693C28](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS24693C28                                |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-066-7327                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS24693-C28 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                               | 2a   |
| <b>Thread Direction:</b>                           | Right-hand   |
| <b>Thread Length:</b>                              | 0.438 Inches Minimum And 0.500 Inches Maximum      |
| <b>Fastener Length:</b>                            | 0.500 Inches Nominal                               |
| <b>Head Style:</b>                                 | Flat Countersunk                                   |
| <b>Head Diameter:</b>                              | 0.238 Inches Minimum And 0.279 Inches Maximum      |
| <b>Internal Drive Style:</b>                       | Cross Recess Type 1                                |
| <b>End Item Identification:</b>                    | Mrap - M-atv With Cs13 Pop And Sne                 |
| <b>Nominal Thread Diameter:</b>                    | 0.138 Inches                                       |
| <b>Thread Quantity Per Inch:</b>                   | 32   |
| <b>Minimum Tensile Strength:</b>                   | 80000 Pounds Per Square Inch                       |
| <b>Countersink Angle:</b>                          | 99.0 Degrees Minimum And 101.0 Degrees Maximum     |
| <b>Screw Material:</b>                             | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 |
| <b>Screw Material Document And Classification:</b> | 66 Fed Std All Material Responses                  |
| <b>Screw Surface Treatment:</b>                    | Passivate  |
| <b>Thread Series Designator:</b>                   | Unc  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.