

## P/N MS24693-C420

## **Description**

Fastener Length: 3/16", Thread: 0-80, Thread Length: 5/32", MS24693 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

### MS24693C420

SKU / Model: MS24693C420

Minimum Qty (MOQ): 100

NSN: 5305-01-223-2637

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS24693-C420 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.106 Inches Minimum And 0.163 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.096 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And Yl3c Style
Departure From Cited Document:	As Modified By Finish Specification

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693-C420">https://military-fasteners.com/screws/machine+screws/MS24693-C420</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24693-C420">https://military-fasteners.com/screws/machine+screws/MS24693-C420</a> and selecting the quantity you