

Description

Fastener Length: 1/2", Thread: 0-80, Thread Length: 15/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693C424](#)

SKU / Model:	MS24693C424
Minimum Qty (MOQ):	15
NSN:	5305-01-372-0074
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS24693-C424 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.418 Inches Minimum And 0.474 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.096 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	A000 Fed Std 3rd Material Response And A000 Fed Std 10th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C424> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.