

Description

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-19/64", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693C57](#)

SKU / Model:	MS24693C57
Minimum Qty (MOQ):	20
NSN:	5305-01-307-2607
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS24693-C57 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.303 Inches Nominal
Fastener Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.308 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1120 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303
Screw Material Document And Classification:	Fed-std 66 Fed Spec All Material Responses
Thread Series Designator:	Unc
Specification/standard Data:	96906-ms24693 Government Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C57> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.