

## P/N MS24693-C57

### **Description**

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-19/64", MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### MS24693C57

SKU / Model: MS24693C57

Minimum Qty (MOQ): 20

NSN: 5305-01-307-2607

Schedule B: 7318.15.6080

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24693-C57 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.303 Inches Nominal
Fastener Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.308 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1120 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303
Screw Material Document And Classification:	Fed-std 66 Fed Spec All Material Responses
Thread Series Designator:	Unc
Specification/standard Data:	96906-ms24693 Government Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24693-C57">https://military-fasteners.com/screws/machine+screws/MS24693-C57</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24693-C57">https://military-fasteners.com/screws/machine+screws/MS24693-C57</a> and selecting the quantity you