

**Description**

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-19/64", MS24693 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS24693C57](#)

SKU / Model:

MS24693C57

Minimum Qty (MOQ):

20

NSN:

5305-01-307-2607

Schedule B:

7318.15.6080

ECCN:

EAR99



\* See page 2 for technical characteristics

## P/N MS24693-C57 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.303 Inches Nominal
<b>Fastener Length:</b>	1.313 Inches Minimum And 1.375 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.308 Inches Minimum And 0.332 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	1120 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303
<b>Screw Material Document And Classification:</b>	Fed-std 66 Fed Spec All Material Responses
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	96906-ms24693 Government Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C57> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.