



Military-Fasteners.com

P/N MS24693-C64

Description

Fastener Length: 2-1/2", Thread: 8-32, Thread Length: 2-13/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS24693C64 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-902-2142 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693-C64 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 2.344 Inches Minimum And 2.406 Inches Maximum |
| Fastener Length: | 2.406 Inches Minimum And 2.500 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.285 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | 66 Fed Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-C64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.