

P/N MS24693-C66

Description

Fastener Length: 2-63/64", Thread: 8-32, Thread Length: 2-29/32", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693C66

SKU / Model: MS24693C66

Minimum Qty (MOQ): 25

NSN: 5305-00-902-2143

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS24693-C66 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	2.844 Inches Minimum And 2.906 Inches Maximum
Fastener Length:	2.906 Inches Minimum And 3.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.285 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693-C66 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS24693-C66 and selecting the quantity you