

Description

MS24693-CB1 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24693CB1](#)

| | |
|-------------------------|---|
| SKU / Model: | MS24693CB1 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-107-9228 |
| Schedule B: | 7318.15.2000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS24693-CB1 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.058 Inches Minimum And 0.139 Inches Maximum |
| Fastener Length: | 0.157 Inches Minimum And 0.188 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.191 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec All Material Responses Or Qq-w-321 Fed Spec All Material Responses Or Qq-b-613 Fed Spec All Material Responses Or Qq-b-637 Fed Spec All Material Responses |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-CB1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.