

Description

Fastener Length: 5/8", Thread: 5/16-18, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693CB117](#)

SKU / Model:	MS24693CB117
Minimum Qty (MOQ):	10
NSN:	5305-01-522-9906
Schedule B:	7415.33.8050
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS24693-CB117 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.484 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.600 Inches Minimum And 0.635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Boeing 575, Aircraft
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	2880 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper
Screw Material Document And Classification:	Astm B16 Assn Std Single Material Response And Astm B36 Assn Std Single Material Response And Astm B134 Assn Std Single Material Response And Astm B206 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response
Special Features:	Faa Certified
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-CB117> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.