

P/N MS24693-CB117

Description

Fastener Length: 5/8", Thread: 5/16-18, Thread Length: 1/2

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693CB117

| SKU / Model: | MS24693CB117 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-522-9906 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |



^{*} See page 2 for technical characteristics

P/N MS24693-CB117 Specifications

| Thread Class: | 2a |
|--|---|
| | |
| Thread Direction: | Right-hand |
| Thread Length: | 0.484 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 0.594 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.600 Inches Minimum And 0.635 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | Boeing 575, Aircraft |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 2880 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Copper |
| Screw Material Document And Classification: | Astm B16 Assn Std Single Material Response And Astm B36 Assn Std Single Material Response And Astm B134 Assn Std Single Material Response And Astm B206 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response |
| Special Features: | Faa Certified |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693-CB117 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.