

P/N MS24693-CB70

Description

Fastener Length: 3/8", Thread: 10-24, Thread Length: 13/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24693CB70

SKU / Model: MS24693CB70

Minimum Qty (MOQ): 145

NSN: 5305-00-054-4997

Schedule B: 7415.33.8050

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N MS24693-CB70 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.209 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.333 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:howitzer, M102; Helicopter, Uh-60a/uh-60d; Aircraft, Hercules C-130; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type Or 3c Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24693-CB70 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.