

Description

Fastener Length: 9/64", Thread: 2-56, Thread Length: 5/64", MS24693 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24693S17](#)

SKU / Model:	MS24693S17
Minimum Qty (MOQ):	100
NSN:	5305-01-276-1609
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-S17 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.067 Inches Minimum And 0.156 Inches Maximum
Fastener Length:	0.140 Inches Minimum And 0.156 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.143 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1013 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1017 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020 Or Steel Comp 1021 Or Steel Comp 1022 Or Steel Comp 1023 Or Steel Comp 1025 Or Steel Comp 1026 Or Steel Comp 1029 Or Steel Comp 1030 Or Steel Comp 1033 Or Steel Comp 1034 Or Steel Comp 1035 Or Steel Comp 1037 Or Steel Comp 1039 Or Steel Comp 1040
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.