

**Description**

Fastener Length: 3/8", Thread: 6-40, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693S226](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS24693S226                               |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-411-0696                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS24693-S226 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.234 Inches Minimum And 0.315 Inches Maximum         |
| <b>Fastener Length:</b>                                     | 0.344 Inches Minimum And 0.375 Inches Maximum         |
| <b>Head Style:</b>  | Flat Countersunk                                      |
| <b>Head Diameter:</b>                                       | 0.238 Inches Minimum And 0.279 Inches Maximum         |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                   |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 40  |
| <b>Minimum Tensile Strength:</b>                            | 60000 Pounds Per Square Inch                          |
| <b>Countersink Angle:</b>                                   | 99.0 Degrees Minimum And 101.0 Degrees Maximum        |
| <b>Screw Material:</b>                                      | Steel   |
| <b>Screw Material Document And Classification:</b>          | Astm A108 Comp 1010 Assn Std Single Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses   |
| <b>Thread Series Designator:</b>                            | Unf   |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type Or 3c Style                                    |
| <b>Departure From Cited Designator:</b>                     | As Modified By Matl                                   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S226> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.