

Description

Fastener Length: 3/8", Thread: 6-40, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24693S226](#)

SKU / Model:	MS24693S226
Minimum Qty (MOQ):	100
NSN:	5305-00-411-0696
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24693-S226 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.234 Inches Minimum And 0.315 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.238 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Astm A108 Comp 1010 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type Or 3c Style
Departure From Cited Designator:	As Modified By Matl

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24693-S226> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.